

FOR PROFESSIONAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN

## Green Lawnger<sup>®</sup>

Turf paint and divot mix colourant

A permanent green paint of turf use

- Adds healthy appearance to warm – and cool – season turf grasses
  - Will not wash off or wear off turf
  - Application on dormant turf lasts through winter
    - Non-phytotoxic to turf
- Recommended for athletic fields, golf courses, commercial and residential lawns

BASF Australia Ltd ABN 62 008 437 867  
Level 12, 28 Freshwater Place Southbank VICTORIA 3006, AUSTRALIA  
Website: [www.agro.basf.com.au](http://www.agro.basf.com.au)

BASF New Zealand Ltd 110297  
3 Airpark Drive, Airport Oaks, MANKAU 2022, NEW ZEALAND  
Website: [www.agro.basf.com.nz](http://www.agro.basf.com.nz)

Customer Service Hotline: 1800 558 399

**DIRECTIONS FOR USE**

Before applying Green Lawnnger®, mow turf area to desired height. 1L of Green Lawnnger covers between 100 and 300m<sup>2</sup> of turf. The wide coverage range is due to the type of condition of grass being treated, and turf colour desired.

For fall application on dormant turf, dilute 1L of Green Lawnnger with 7 to 9 L of water. For a darker colour, a lower volume of water is recommended. Some experimentation may be required with ratios.

For summer application on discoloured turf, dilute 1L with 15 to 20 L of water. Rate depends on desired colour. For best results on discoloured areas, two applications are recommended to blend the applied area with the existing healthy turf.

**EQUIPMENT NOTICE**

BASF recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawnnger in centrifugal pumps. Standard ceramic seals may leak during operation. A spray shield is recommended for application if overspray or drift is a potential problem. Avoid overspray on concrete, masonry, or any other objects where colour is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent rub-off on uniforms, allow Green Lawnnger to dry prior to using athletic field. Rinse spray tank. Spray nozzles, and screens thoroughly with water immediately following use. For best results, use low to medium sprayer pressure.

**DIVOT MIX SAND**

Mix 200mL of Green Lawnnger with the same volume of water. Spray or pour the solution onto 50kg of divot mix sand in a cement-type mixer.

**PRECAUTIONS**

Keep out of reach of children. Avoid contact with the eyes and skin. See MSDS for further information.

**WARRANTY**

The statements on this label are believed to be true and accurate, but because use conditions are beyond our control, BASF, does not make, nor does it authorize any agent or representative to make any oral or written warranty, guarantee, or representation, expressed or implied, concerning this material or the use thereof beyond the statements of the label. Neither BASF, nor the seller shall be held responsible in any manner for any claim, personal injury, or property damage or loss resulting from handling, storage, or use of this material not in accordance with the written directions. The buyer assumes all risk and liability resulting from handling, storage, or use, and purchaser accepts and uses this material on these conditions. No other warranty exists.

Batch No:

Date of Manufacture:

BASF Australia Ltd  
ABN 62 008 437 867  
Level 12, 28 Freshwater Place  
Southbank VICTORIA 3006  
AUSTRALIA

FOR SPECIALIST ADVICE IN AN EMERGENCY ONLY PHONE 1800 803 440 TOLL FREE – ALL HOURS – AUSTRALIA WIDE

BASF New Zealand Ltd  
110297  
3 Airpark Drive,  
Airport Oaks, MANKAU 2022,  
NEW ZEALAND

EMERGENCY PHONELINK 0800944 955 TOLL FREE – ALL HOURS – NEW ZEALAND WIDE